

205 UREA/DEF Trolley & Pump Kit

DKB242400 / DKB022400



DKB242400(12 Volt DC)



DKB022400(240 Volt AC)

FEATURES	DKB242400	DKB022400
Voltage AC [V, Hz]:	12	240, 50
Current max [A]:	20	1,95
Power [W]:	200	350
Motor protection	IP55	IP55
On/Off switch	Yes	Yes
Cable [m]:	4	2
Duty cycle [min]:	S2 20	S2 20
Flow rate max [LPM / GPM]:	4 - 24 / 1 - 6	4 - 24 / 1 - 6
Pression Max [bar]:	1,9	1,5
Suction dry height [m]:	2	2
By-Pass valve:	Yes	Yes
Built in filter [µm]:	No	No
Flow selector:	Yes	Yes
Suction hose [material, ø, m]:	Rubber, 20, 1,5	Rubber, 20, 1,5
Delivery hose [material, ø, m]:	Rubber, 20, 4,5	Rubber, 20, 4,5
Hosereel:	No	No
Nozzle:	Automatic	Automatic
IBC valve:	Included	Included
Telescopic hose for tank:	Included	Included
Meter:	Turbine	Turbine
Precision[%]:	± 0,5	± 0,5
Repeatability [%]:	0,2	0,2
Seal material:	Viton	Viton
Temperature min/max [°C]:	-5 / +40	-5 / +40
Allowed fluids:	UREA/DEF, AUS 32, Water	UREA/DEF, AUS 32, Water
Forbidden fluids:	Gas, Alcohol, Gasoline, Diesel, Kerosene	
Noise 1 m [dB]:	70	70
Net weight [Kg]:	35	35
Gross weight [Kg]:	38	38